



## Product Identification

**4500/MW2**

Mechanic Sanitarblock

## Definition and Application

Pre-assembled structure for installation in front of masonry wall and finish in light wall, plasterboard wall and technical support rail for light wall  
Compatible with all wall-hung WC pans

## Technical Features

### **Structure**

In painted tubular corrosion resistant  
Easy and quick installation with Fast Fit system  
Minimum thickness of 126mm and adjustable up to 170mm  
Height regulation of the adjustable floor brackets (0-200 mm);  
Depth adjustable outlet bend  
Tested for 400kg load

### **Cistern**

Dual flush in-wall cistern compatible with either dual or single flush actuators 6/3 litres (adjustable to 4/2 and 7/3)  
126mm thickness  
Mechanic actuation  
Piston Inlet Valve  
Silent valve Class 1 (NF certified)

# Technical Sheet

## Mechanic Sanitarblock

Working pressure from 0,1 to 16 bar  
Resistance to atmospheric humidity (Hr <90%).  
Polypropylene (PP) cistern highly resistant and inalterable to thermal stress  
CE EN 14055 marking CL1  
Supplied with anti-condensation lining

### Accessories

- 1 Flush pipe ø90 x 250
- 1 Seal for flush pipe ø125
- 1 Connecting pipe ø45 x 180
- 1 Pan rubber seal ø45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush bend ø 90 / 90 L230
- 1 Outlet bend and Ø90/110 adaptor
- 1 Protection pipe Ø90

### Fixing accessories for wall structure:

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing for metal structure

### For fixing cistern on the structure:

- 2 Threaded rods M12
- 2 Nuts M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Washers Zn ø 34

## Warranty

10 years of warranty.  
The warranty is not valid in case the product is not installed according to the installation instructions.